

ADVANCING TABULAR SYNTHETIC DATA GENERATION FOR CRITICAL DOMAINS

Synthesizing Heavy and Mixed Tail Data

- Real world data have a mix of heavy and light tail behavior
- The generative model needs to capture the tail behavior of the real data accurately
- It is necessary for correctly generate rare cases without generating non-existent anomalous data
- Most of the available literature do not address this issue directly
- Our solution: make Normalizing Flows tail adaptive without any pre-assumptions about the tail behavior of the target density
- Results:
- Amiri, Saba, et al. "Compressive differentially private federated learning through universal vector quantization." AAAI Workshop on Privacy -Preserving Artificial Intelligence. 2021.
- Amiri, Saba, et al. "On the impact of non-IID data on the performance and fairness of differentially private federated learning." 2022 52nd Annual IEEE/IFIP International Conference on Dependable Systems and Networks Workshops (DSN-W). IEEE, 2022.
- Amiri, Saba, et al. "Generating Heavy-Tailed Synthetic Data with Normalizing Flows." The 5th Workshop on Tractable Probabilistic Modeling. 2022.
- Amiri, Saba, et al. "Practical Synthesis of Mixed-Tailed Data with Normalizing Flows", working paper

Synthesizing Semantically Correct Data

- Probabilistic generative models for synthesizing data
- These models could potentially generate samples that are in the support of their estimated distribution but are semantically incorrect, e.g. a male patient with pregnancy history
- The semantic rules are mostly either undocumented or unidentified
- A way to model the semantic boundaries of the variables in an unsupervised manner
- Use extracted boundaries to guide the generative model during the training/inference phase
- Our solution: add an independent validator component to the data synthesizer to model and enforce semantic rules
- Results:
 - Amiri, Saba, et al. "Differential Privacy vs Detecting Copyright Infringement: A Case Study with Normalizing Flows.". Gen Law 23. ICML
 - Amiri, Saba, et al. "Synthesizing Tabular Data with Regularized Latent Representations for Improved Semantic Integrity", working paper

Synthesizing Private Data

- Models trained on real data are vulnerable to adversarial attacks such as membership inference, could potentially leak training data
- Synthetic data could potentially let an adversary gain information about the training set and/or reconstruct it
- We need privacy preserving generative models with provable privacy guarantees
- We aim to make the generative models differentially private
- Differential privacy has a performance and/or fairness cost
- Our solution: Noiseless differentially private normalizing flows
- Results:
- Amiri, Saba, et al. " Noise-less differentially private normalizing flows for tabular data synthesis", working paper